

## Dräger PIR 3000 Detection of flammable gases and vapours

The Dräger PIR 3000 is an explosion proof infrared gas detector for continuous monitoring of combustible gases and vapors. Based on a stainless steel SS 316 enclosure as well as on a good measuring performance, this transmitter offers an excellent price-performance-ratio.



## Benefits

---

### Failsafe infrared technology and low cost of ownership

The superior performance characteristics of infrared technology (such as poison immune and "fail-safe" operation) have been known and valued in gas detection for many years. The PIR 3000 now offers these performance benefits more affordably, combined with low maintenance costs and a long life time of more than 15 years, cost of ownership is significantly reduced.

---

### Smart and flexible

The PIR 3000 offers a gas library with three gas categories: methane, propane and ethylene. Therefore, nearly all hydrocarbons are detectable. In addition, temperature-compensated linearisation curves allow for signal output for individual substances. Through optional accessories – e.g. the process adapter or the duct mount set – a multitude of measuring tasks can be performed professionally.

---

### Suitable for the harshest conditions

Based on its exceptional product quality, the PIR 3000 offers high reliability and excellent measuring performance, in relation to long-term stability. With GRP junction box and 316 stainless steel enclosure, a temperature range of - 40 to + 65 °C (- 40 to + 149 °F) and heated measurement optics driving off compensation from the lens, the PIR 3000 is suitable for all the worlds climate zones.

---

### Performance features

- Temperature-compensated and non-imaging optics
- Gas library with 3 gas categories: Methane, propane and ethylene (typical of most hydrocarbons), performance approved in accordance with IEC 60079
- Performance approval (in accordance with IEC 60079) for 13 further substances
- Dirt and dust protection through hydrophobic splash guard
- Analog 4 to 20 mA output signal (universal)
- Specified temperature range from - 40 °C to + 65 °C / - 40 °F to + 149 °F
- Unrestricted usage in humid atmospheres
- Hermetically sealed 316 stainless steel enclosure
- Slim enclosure design for confined areas of use
- Long maintenance interval thanks to minimum long-term drift
- No moving parts
- Typical life time: 15 years
- Ex approvals for worldwide use: ATEX, IECEx, UL, CSA
- Dust ex approval for zone 21 and 22
- Ingress Protection: IP 65, IP 66 and IP 67

## System Components



D-6806-2016

### Dräger REGARD® 7000

The Dräger REGARD® 7000 is a modular and therefore highly expandable analysis system for monitoring various gases and vapours. Suitable for gas warning systems with various levels of complexity and numbers of transmitters, the Dräger REGARD® 7000 also features exceptional reliability and efficiency. An additional benefit is the backward compatibility with the REGARD®.



ST-335-2004

### Dräger REGARD®-1

The Dräger REGARD®-1 is a standalone, self contained single channel control system for the detection of Toxic, Oxygen and Ex hazards. The control system is fully configurable for a single input from either a 4 to 20 mA transmitter or a Dräger Polytron® SE Ex measuring head.



D-27771-2009

### Dräger REGARD® 3900

The Dräger REGARD® 3900 is a standalone, self contained control system for the detection of Toxic, Oxygen and Ex hazards. The control system is fully configurable between 1 and 16 channels, depending upon the type and quantity of input/output boards installed.

## Accessories



### Splash guard

Guards the measuring cuvette against dirt and dust, water-repellent, fitted as standard. Order No.: 68 10 796



### Process adapter

Sampling or process applications with gas inlet and outlet. Order No.: 68 11 330



### Calibration adapter

Transmitter calibration (with mounted splash guard), up to wind force 10 Bft, fitted as standard. Order No.: 68 10 859



### Weather Guard

Double-walled enclosure to prevent dirt deposits, e.g. salt crust. Improves resistance to extreme weather conditions. Order No.: 68 11 135

## Related Products

D-32406-2011



### Dräger Polytron® 5310 IR

The Dräger Polytron® 5310 IR is a cost effective explosion-proof transmitter for the detection of flammable gases in the lower explosion limit (LEL). It uses an infrared DrägerSensor® IR that can be configured for methane, propane, or ethylene. A 3-wire 4 to 20-mA analogue output with relays makes it compatible with most control systems.

ST-11659-2007



### Dräger PIR 7000

The Dräger PIR 7000 is an explosion proof point infrared gas detector for continuous monitoring of flammable gases and vapours. With its stainless steel SS 316L enclosure and drift-free optics this detector is built for the harshest industrial environments, e.g. offshore installations.

D-11168-2011



### Dräger PEX 3000

The transmitter Dräger PEX 3000 detects flammable gases and vapours in concentrations below their lower explosive limit. Its DD-sensor provides a long-term stable measuring signal and responds to gas within a few seconds.

## Technical Data

Type	Explosion proof gas detector with infrared sensor technology	
Working principle	Temperature-compensated infrared absorption	
Gases and ranges	Methane, propane, ethylene: 0 to 100 %LEL (further substances on request)	
Measuring performance (Methane)	Digital resolution	0.5 %LEL
	Repeatability	$\leq \pm 2$ %LEL
	Response time $t_{0..90}$	$\leq 30$ seconds (with splash guard and calibration adapter)
Electrical data	Output signal	4 to 20 mA
	Fault signal	1 mA
	Power supply	10 to 30 V DC
	Power consumption	$\leq 2$ W
Ambient conditions	Temperature	- 40 to + 65 °C / - 40 to + 150 °F
	Pressure	700 to 1300 hPa / 23.6 to 32.5 inch Hg
	Humidity	0 to 100 %RH
Enclosure	Material	Stainless steel SS 316
	Connecting thread	M25 or 3/4" NPT
	Weight	550 g
	Size	170 mm x $\varnothing$ 37 mm / 6.7" x $\varnothing$ 1.45"
	Ingress protection	IP 65, IP 66 and IP 67
Approvals	ATEX	II 2G Ex d(e) IIC T6, II 2D Ex tD A21 IP6X T80 °C
	IECEX	Ex d(e) IIC T6, Ex tD A21 IP6X T80 °C
	UL	Class I, Div. 1, Groups A, B, C, D, Class II, Div. 1, Groups E, F, G
	CSA	Class I, Div. 1, Groups A, B, C, D
	CE mark: electromagnetic compatibility (directive 89/336/EEC)	

## Ordering Information

Dräger PIR 3000 (M25)	68 10 810
Dräger PIR 3000 (NPT)	68 11 080
Dräger PIR 3000 complete set e	68 11 160
Dräger PIR 3000 complete set e2	68 11 270
Dräger PIR 3000 complete set d	68 11 180

All transmitters are equipped with splash guard and calibration adapter.

The complete set contains a junction box, already pre-assembled.

## Notes

## Notes

Not all products, features, or services are for sale in all countries.  
Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to [www.draeger.com/trademarks](http://www.draeger.com/trademarks) to find the current status.

### **CORPORATE HEADQUARTERS**

Drägerwerk AG & Co. KGaA  
Moislinger Allee 53–55  
23558 Lübeck, Germany  
[www.draeger.com](http://www.draeger.com)

### **REGION DACH**

Dräger Safety AG & Co. KGaA  
Revalstraße 1  
23560 Lübeck, Germany  
Tel +49 451 882 0  
Fax +49 451 882 2080  
[info@draeger.com](mailto:info@draeger.com)

### **REGION EUROPE**

Dräger Safety AG & Co. KGaA  
Revalstraße 1  
23560 Lübeck, Germany  
Tel +49 451 882 0  
Fax +49 451 882 2080  
[info@draeger.com](mailto:info@draeger.com)

### **REGION MIDDLE EAST, AFRICA**

Dräger Safety AG & Co. KGaA  
Branch Office  
P.O. Box 505108  
Dubai, United Arab Emirates  
Tel +971 4 4294 600  
Fax +971 4 4294 699  
[contactuae@draeger.com](mailto:contactuae@draeger.com)

### **REGION ASIA PACIFIC**

Draeger Singapore Pte. Ltd.  
25 International Business Park  
#04-20/21 German Centre  
Singapore 609916  
Tel +65 6308 9400  
Fax +65 6308 9401  
[asia.pacific@draeger.com](mailto:asia.pacific@draeger.com)

### **REGION CENTRAL AND SOUTH AMERICA**

Dräger Panama S. de R.L.  
Complejo Business Park,  
V tower, 10th floor  
Panama City  
Tel +507 377-9100  
Fax +507 377-9130  
[contactcsa@draeger.com](mailto:contactcsa@draeger.com)

Locate your Regional Sales  
Representative at:  
[www.draeger.com/contact](http://www.draeger.com/contact)

