

Dräger REGARD® 2400 and REGARD® 2410 Control System

Dräger REGARD® 2400 and 2410 are flexible small control units for detection of toxic gases and oxygen as well as combustible gases and vapours. Combined with the Dräger transmitters or sensing heads Dräger REGARD® 2400 or 2410 forms a low-maintenance gas detection system for reliable protection.



Benefits

Versions and configuration

Up to four transmitters can be connected to the REGARD 2400 and REGARD 2410 control systems. The REGARD 2400 comes with an enclosure with integral power supply unit and can be mounted directly to a wall. The REGARD 2410 has been designed for economical mounting on DIN rails in existing switch or wall cabinets. Both versions have four integrated relays which are assigned to the two gas alarms, audible warning and fault condition. In addition to the four inputs for transmitters, the REGARD 2400/2410 also provide two digital inputs. This can be used for remote acknowledgement for example. Both devices have ATEX approval.

Easy to operate

The configuration of the REGARD 2400/2410 is carried out via a laptop or a PC. The appropriate connection cable and the required software are available as accessories.

Flexible extensions

Via the internal Modbus interface, the REGARD 2400 and 2410 can be connected with external modules such as an input or output module or one or several relay modules.

System Components



Dräger PIR 7000

The Dräger PIR 7000 is an explosion proof point infrared gas detector for continuous monitoring of flammable gases and vapours. With its stainless steel SS 316L enclosure and drift-free optics this detector is built for the harshest industrial environments, e.g. offshore installations.

System Components



ST-3812-2003

Dräger Polytron® 7000

The Dräger Polytron® 7000 is a gas detector that can satisfy many toxic and oxygen gas measurement applications on a single platform. It meets the requirements of the compliance market as well as the high specification requirements of customised solutions.



D-11158-2011

Dräger PEX 3000

The transmitter Dräger PEX 3000 detects flammable gases and vapours in concentrations below their lower explosive limit. Its DD-sensor provides a long-term stable measuring signal and responds to gas within a few seconds.

Related Products



D-2777-2009

Dräger REGARD® 3900

The Dräger REGARD® 3900 is a standalone, self contained control system for the detection of Toxic, Oxygen and Ex hazards. The control system is fully configurable between 1 and 16 channels, depending upon the type and quantity of input/output boards installed.

Related Products



ST-335-2004

Dräger REGARD®-1

The Dräger REGARD®-1 is a standalone, self contained single channel control system for the detection of Toxic, Oxygen and Ex hazards. The control system is fully configurable for a single input from either a 4 to 20 mA transmitter or a Dräger Polytron® SE Ex measuring head.



D-6806-2016

Dräger REGARD® 7000

The Dräger REGARD® 7000 is a modular and therefore highly expandable analysis system for monitoring various gases and vapours. Suitable for gas warning systems with various levels of complexity and numbers of transmitters, the Dräger REGARD® 7000 also features exceptional reliability and efficiency. An additional benefit is the backward compatibility with the REGARD®.

Technical Data

Central unit	Independent 4-channel wall-mounted (2400) or rail-mounted (2410) control unit in accordance with DIN EN 50022	
Power supply	24 VDC +/- 10 % (2410) 24 VDC / 110 to 230 VAC 50 to 60 Hz (2400)	
Inputs	2-wire/3-wire 4 to 20 mA transmitter or Dräger Polytron SE Ex sensing heads via signal converter (optional)	
Outputs	Potential-free relay contacts of the 2 gas alarm relays plus one acoustic alarm relay and one failure relay each for 250 VAC, 2 A (2400 DPCO and 2410 SPCO)	
Ambient conditions	Temperature	- 20 to + 60 °C
	Atmospheric pressure	700 to 1300 hPa
	Atmospheric humidity	10 to 90 %, non-condensing
User interface	3-pushbutton operation Dot-matrix display, LEDs RS 232 for configuration software Modbus interface	
Dimensions	Dräger REGARD® 2410	105 x 86 x 72 mm (W x H x D)
	Dräger REGARD® 2400	185 x 213 x 118 mm (W x H x D)
Ingress protection	Dräger REGARD® 2410	IP 20
	Dräger REGARD® 2400	IP54
Approvals	ATEX	
	Ex II (2)G, TPS 14 ATEX 1 672 X According to EN 60079-0:2012, EN 60079-0/A11:2013, EN 60079-29-1:2007, EN 50271:2010 and EN 50104:2010	
CE markings	Electromagnetic Compatibility (Directive 2014/30/EU; EN 50270:2006) Low Voltage (Directive 2014/35/EU; EN 61010-1:2010)	
Functional Safety	SIL 1	

Ordering Information

Dräger REGARD® 2410	SC 00 011
Dräger REGARD® 2400	SC 00 014
Internal converter module SE Ex (only Dräger REGARD® 2400), one required per SE Ex channel	SC 00 016
Converter module SE Ex, one required per SE Ex channel	36 03 560
Configuration set	SC 00 040
Input-Output module	SC 00 018
Relay module	SC 00 019
Power Supply 2.5A, DIN Rail Mounting	42 08 745
Power Supply 5A, DIN Rail Mounting	42 08 746
Power Supply 8A, DIN Rail Mounting	42 08 747

Notes

Not all products, features, or services are for sale in all countries.
Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
www.draeger.com

REGION DACH

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION EUROPE

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
Tel +971 4 4294 600
Fax +971 4 4294 699
contactuae@draeger.com

REGION ASIA PACIFIC

Draeger Singapore Pte. Ltd.
25 International Business Park
#04-20/21 German Centre
Singapore 609916
Tel +65 6308 9400
Fax +65 6308 9401
asia.pacific@draeger.com

REGION CENTRAL AND SOUTH AMERICA

Dräger Panama S. de R.L.
Complejo Business Park,
V tower, 10th floor
Panama City
Tel +507 377-9100
Fax +507 377-9130
contactcsa@draeger.com

Locate your Regional Sales
Representative at:
www.draeger.com/contact

