

WORKSAFE INTRINSIC LIGHTHAWK GEN II

Model Numbers on Back

SUPER-LIGHTWEIGHT, FULL-SIZE, LONG RANGE RECHARGEABLE LANTERN

- 447 meter beam reach
- Dual Mode Spot Beam: High /Low
- Steady-on/ flashing modes and rear signaling tail light
- Waterproof and submersible
- Low battery indication: red for charging, green for fully charged
- Articulated head
- Intrinsically safe







CONSTRUCTED OF TOUGH NYLON, WITH A NON-SLIP RUBBER BOTTOM AND HANDLE.



FLI STANDARDS 300 LUMENS 7 h / 14 h 70,000 cd 447m 1m

SPECIFICATIONS

POWER SOURCE: 4 CELL Lithium Ion Rechargeable Battery

LAMP: Advanced LED Technology

LIGHT OUTPUT: 300 Lumens on High/125 Lumens on Low

PEAK BEAM INTENSITY: 70,000 candela

BEAM DISTANCE: 447 Meters

RUN TIME: 7 Hours on High/ 14 Hours on Low

WEIGHT: 1.9 lbs

LENGTH: 9.5 in. WIDTH: 3.12 in. HEIGHT: 5.12 in.

COLORS: Safety Orange, Yellow, Black **OPERATING TEMP:** -20°C to 50°C

SAFETY RATINGS

Intrinsically Safe

UL Protection Methods
UL 913 CSA C22.2 No 157

Class I, II, III, Division 1, Groups C - G, T1 Class I, II, III, Division 2, Groups A - G, T5

Ingress Protection Level: IP67

Meets NFPA 1901 14.1.11.2 2003 Edition

