

**ZONE 1/21
CL I, II, III DIV 1**



13-pin ISM interface



**Android™ 10
Upgrade to Android™ 13
(available Q3/2023)**

**Zero-touch capable
MDM compatible**

IS530.1

Android
Enterprise
Recommended



The high-performance industrial smartphone can be used in a variety of ways thanks to the ISM interface. Additional modules such as an RSM, PTT headsets, the professional IS-TH1xx.1 barcode scanner and the thermal camera IS-TC1A.1 make the IS530.1 a high-performance multifunctional device. The smartphone is Android Enterprise Recommended, zero-touch capable and MDM compatible.

› Android is a trademark of Google LLC. All trademarks and copyrights are the properties of their respective owners. › © 2023 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1029MD01REV15_EN_09.2023



< IS530.1 >



ATEX approval: EX-Zone 1/21
Ⓜ II 2G Ex ib IIC T4 Gb
Ⓜ II 2D Ex ib IIIC T135°C Db IP6X



IECEx approval: EX-Zone 1/21
Ex ib IIC T4 Gb
Ex ib IIIC T135°C Db IP6X



NEC500 approval:
Class I, II, III Division 1
Groups A B C D E F G T



EAC approval:
1Ex ib IIC T4 Gb X
Ex ib IIIC T135°C Db X IP64

Further approvals: INMETRO (Brazil) | KCs (South Korea) | PCEC (China) | JNIOOSH (Japan) | SANS (South Africa)

TECHNICAL FEATURES

Operating system	Android™ 10 Upgrade to Android™ 13 (available Q3/2023)
Processor	SDM660 Octa-Core (Kryo Gold-Quad cores 2,2 GHz; Kryo Silver-Quad cores 1,8 GHz)
Memory	4 GB RAM 64 GB internal memory microSD memory up to 128 GB
Frequencies	2G GSM: 850/900/1800/1900 MHz 3G WCDMA: UMTS B1/2/4/5/8 4G LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/26/28A/28B/29/30/66 4G LTE-TDD: B38/B39/B40/B41 4G LTE-SCDMA: B34/B39
Dimensions	size: 155 x 80 x 25 mm weight: 325 g
Display	4,5" Gorilla Glass® 3. generation 854 x 480 pixels
Battery	3600 mAh, 3,8 V, 13,68 Wh replaceable
Camera	13 MP AF rear camera 5 MP FF front camera
Connections	WiFi 2,4 GHz + 5 GHz: IEEE 802.11 a/b/g/n/ac/e/k/r/h with max. 8 connections hotspot Bluetooth® 5 GPS, A-GPS, Glonass, Beidou, Galileo Near Field Communication
Types of protection	IP68 dust-/waterproof MIL-STD-810G usable from -20 °C to +60 °C

FURTHER FEATURES



SOS key for loneworker protection
LWP ready (third party application required,
based on country specific regulations)



13-pin ISM interface for a quick and safe
connection of additional devices for a
wide range of applications



Dual micro-SIM



Amplified loudspeaker



Magnetic charger port



Accelerometer, gyroscope, light, magnetic,
proximity, pressure sensors

SET CONTENT

Smartphone, Battery, i.safe PROTECTOR 2.0 Type C USB Cable, i.safe PROTECTOR 3.0 USB Magnetic Charger Cable, Power Adapter universal, Screwdriver, Display Protection Foil, Quick Start Manual and Safety Instructions

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.